

Capacitor Replacement List

Device: Sony CR45-S PSU for the Macintosh IIfx

Group	Location	Capacitance	Voltage	Diameter	Length	Leads
Main	C105	680 μ F	250 V	25mm	40mm	12mm
	C106	680 μ F	250 V	25mm	40mm	12mm
	C109	4.7 μ F	400 V	10mm	20mm	5mm
	C213	10000 μ F	6.3 V	16mm	32mm	8mm
	C212	10000 μ F	6.3 V	16mm	32mm	8mm
	C214	4700 μ F	16 V	16mm	32mm	8mm
	C215	2200 μ F	16 V	12mm	25mm	5mm
	C219	100 μ F	25 V	6mm	11mm	3mm
	C220	100 μ F	25 V	6mm	11mm	3mm
	C221	1000 μ F	16 V	10mm	16mm	5mm
	C208	47 μ F	25 V	5mm	11mm	2mm
	C207	1 μ F	50 V	5mm	11mm	2mm
	C110	47 μ F	25 V	5mm	11mm	3mm
45C	C178	10 μ F	50 V	5mm	11mm	3mm
	C179	10 μ F	50 V	5mm	11mm	3mm
	C173	1 μ F	50 V	5mm	11mm	3mm
	C174	0.47 μ F	50 V	5mm	11mm	3mm
45S9	C302	100 μ F	25 V	5mm	11mm	3mm
	C351	100 μ F	25 V	5mm	11mm	3mm
	C308	100 μ F	25 V	5mm	11mm	3mm
	C304	100 μ F	25 V	5mm	11mm	3mm
	IC303 ¹	2.2 μ F	50 V	5mm	11mm	3mm

¹ CONNECTED TO THE IC DIRECTLY, NEGATIVE ON A AND POSITIVE ON K